

SMAJ Plastic-Encapsulate Diodes

SS22 THRU SS220

Schottky Rectifier Diodes

Features

- $I_{F(AV)}$ 2A
- V_{RRM} 20V-200V
- High surge current capability
- Polarity: Color band denotes cathode


Applications

- Rectifier

Marking

- SS2X

X : From 2 To 20



Limiting Values(Absolute Maximum Rating)

Item	Symbol	Unit	Test Conditions	SS2								
				2	3	4	5	6	8	10	15	20
Repetitive Peak Reverse Voltage	V _{RRM}	V		20	30	40	50	60	80	100	150	200
Maximum RMS Voltage	V _{RMS}	V		14	21	28	35	42	56	70	105	140
Average Forward Current	I _{F(AV)}	A	60Hz Half-sine wave, Resistance load	2.0								
Surge(Non-repetitive)Forward Current	I _{FSM}	A	60Hz Half-sine wave, 1 cycle, Ta=25℃	50								
Junction Temperature	T _J	℃		-55~+125			-55~+150					
Storage Temperature	T _{STG}	℃		-55 ~ +150								

Electrical Characteristics (T =25°C Unless otherwise specified)

Item	Symbol	Unit	Test Condition		SS2								
					2	3	4	5	6	8	10	15	20
Peak Forward Voltage	V _F	V	I _F =2.0A		0.55			0.70		0.85		0.95	
Peak Reverse Current	I _{RRM1}	mA	V _{RM} =V _{RRM}	T _a =25°C	0.5				0.1				
			T _a =100°C	10				5.0					
Thermal Resistance	R _{θJ-A}	°C/ W	Between junction and ambient		88								
	Between junction and terminal		28										
Juction Capacitance (Typical)	C _j	pF	Measured at 1MHZ and Applied Reverse Voltage of 4.0 V.D.C		114			92		53		40	

Notes:

Thermal resistance from junction to ambient and from junction to lead mounted on FR4 PCB double sided copper mini pad

Typical Characteristics

FIG.1: FORWARD CURRENT DERATING CURVE






FIG 2: MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




SS22-SS24

FIG.3: TYPICAL FORWARD CHARACTERISTICS



SS22-SS24


FIG.4: TYPICAL REVERSE CHARACTERISTICS



Typical Characteristics


SS25-SS26

FIG.5: TYPICAL FORWARD CHARACTERISTICS




SS25-SS26

FIG.6: TYPICAL REVERSE CHARACTERISTICS




SS28-SS210

FIG.7: TYPICAL FORWARD CHARACTERISTICS



SS28-SS210


FIG.8: TYPICAL REVERSE CHARACTERISTICS



Typical Characteristics


SS215

FIG.9: TYPICAL FORWARD CHARACTERISTICS




SS215

FIG.10: TYPICAL REVERSE CHARACTERISTICS




SS220

FIG.11: TYPICAL FORWARD CHARACTERISTICS




SS220


FIG.12: TYPICAL REVERSE CHARACTERISTICS



SMAJ Package Outline Dimensions



SMAJ Suggested Pad Layout



Note:

1. Controlling dimension: in millimeters.
2. General tolerance: ± 0.05 mm.
3. The pad layout is for reference purposes only.

NOTICE

JSCJ reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSCJ does not assume any liability arising out of the application or use of any product described herein.

Reel Taping Specifications For Surface Mount Devices-SMAJ




FIG:CONFIGURATION OF SURFACE MOUNTED DEVICES TAPING

ITEM	SYMBOL	SMAJ mm(inch)
Carrier width	A	2.79±0.1(0.110±0.004)
Carrier length	B	5.33±0.1(0.210±0.004)
Carrier depth	C	2.36±0.1(0.093±0.004)
Sprocket hole	d	1.55±0.05(0.061±0.002)
Reel outside diameter	D	279±2.0 (11± 0.079)
Reel inner diameter	D1	75±1.0 (2.95 ±0.039)
Feed hole diameter	D2	13±0.5(0.512±0.020)
Strocket hole position	E	1.75±0.1(0.069±0.004)
Punch hole position	F	5.5±0.05(0.217±0.002)
Punch hole pitch	P	4.0±0.1(0.157±0.004)
Sprocket hole pitch	P0	4.0±0.1(0.157±0.004)
Embossment center	P1	2.0±0.1(0.079±0.004)
Totall tape thickness	T	0.28±0.02(0.011±0.0008)
Tape width	W	12.0±0.2(0.472±0.008)
Reel width	W1	16.8±2.0(0.661±0.079)

NOTE:Devices are packed in accordance with EIA standard RS-481-A and specification given above.